



TG-S606P

Thermal Compound

REACH Compliant RoHS Compliant

Features

- Thermal Conductivity 8 W/mK
- Easy application
- High stability
- Does not harden over time

Applications


Electronic components - IC, CPU, MOS, LED, Motherboard, P/S, Heat sink, LCD TV, Notebook PC, PC Telecom Devices, Wireless hubs, DDR II Module, DVD Applications, Hand-set applications, etc.

Standard Sizes

Syringes	Pot / Pail
30gr	100gr
50gr	500gr
	1.0kg
	1.5kg

Properties

Thermal Conductivity : 8 W/mK



Properties	TG-S606P	Unit	Test Method
Thermal Conductivity	8.0	W/mK	ASTM D5470
Colour	White	-	Visual
Weight Loss	<0.5	%	ASTM E595
Density	2.3	g/cm ³	ASTM D792
Working Temperature Range	-40~+180	° C	-
Volume Resistance	>10 ¹²	Ohm-cm	ASTM D257
Shelf Life	6	months	T-Global

Storage

Thermal grease has a shelf-life of eighteen (18) months from the date of manufacture, as indicated by the lot number, when stored in the original, unopened container at, or below 25°C.

T-Global Technology (Europe & North America) Limited

Units 1-2 Cosford Business Park, Central Park, Lutterworth, Leicestershire, LE17 4QU, United Kingdom
T +44 (0)1455 553 510 **E** sales@tglobaltechnology.com **W** www.tglobaltechnology.com

Version 3
20200629



T-Global Technology are proud to announce the launch of a new company logo and mission statement as part of the ongoing growth and evolution of our company's brand.

NOTICE: The information contained herein is to the best of our knowledge true and accurate. Values stated in this technical data sheet represent typical values as not all tests are run on each lot of material produced. All specifications are subject to change without notice. The protective film does not affect the function of the product. If there is no special requirement, the default depends on T-Global. Since the varied conditions of potential use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part and users should make their own test to determine the suitability of our products in any specific situation. This product is sold without warranty either expressed or implied, of fitness for a particular purpose or otherwise, except that this product shall be of standard quality, and except to the extent otherwise stated in T-Global Technology's invoice, quotation, or order acknowledgment. We disclaim any and all liabilities incurred in connection with the use of information contained herein, or otherwise. All risks of such are assumed by the user. Furthermore, nothing contained herein shall be construed as a recommendation to use any process or to manufacture or to use any product in conflict with existing or future patents covering any product or material or its use.