



TG-PP-10 Silicone Thermal Putty

Version 3.300719

Silicone Thermal Putty

TG-PP-10 is a high-performance silicone putty material which is designed to offer a low cost of ownership approach to thermal management. The product is a one-part, fully cured thixotropic putty which can be dispensed either manually or automatically for volume production. The product is form stable and can be used for applications such as automotive electronics, consumer electronics and medical devices.

Features

- Thermal conductivity 10 W/mK
- Single component silicone putty
- Soft and ultra high compressibility for low stress applications
- Can be used to fill gaps from 0.25 – 8mm

Applications

- Consumer electronics
- White goods
- Telecom infrastructure

Properties

- ✓ REACH Compliant
- ✓ ROHS Compliant

Property	TG-PP-10	Unit	Test Method
Chemical type	Silicone	-	-
Appearance	White Putty	-	-
Mix ratio, by weight	1 component	-	-
Shelf life	6	Month	-
Viscosity, Brookfield RVT, 25 °C	Putty	cP	ASTM D792
Specific gravity, 25 °C	1.2	-	ASTM D792
Thermal Conductivity	10	W / mK	ASTM D5470
Hardness	50	Shore 00	ASTM D2240
Storage Temperature	-50 to 200	°C	-

Storage

Tightly close original container of unused product and store in a dark and cool place.

Standard Packaging

Pot Size	Pot	Weight (gr)
	Pail	1kg
Pail	5kg	

* All measurements in weights are in gr

* Data for design engineer guidance only. Observed performance varies in application. Engineers are reminded to test the material in application.

T-Global Technology Limited
1 & 2 Cosford Business Park, Central Park,
Lutterworth, Leicestershire LE17 4QU U.K.

Tel: +44 (0)1455 553 510
Email: sales@tglobaltechnology.com
Web: www.tglobaltechnology.com
Skype: tglobal.technology
VAT #: GB 116 662 714

NOTICE: The information contained herein is to the best of our knowledge true and accurate. However, since the varied conditions of potential use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part and users should make their own test to determine the suitability of our products in any specific situation. This product is sold without warranty either expressed or implied, of fitness for a particular purpose or otherwise, except that this product shall be of standard quality, and except to the extent otherwise stated in T-Global Technology Europe and North America's invoice, quotation, or order acknowledgment. We disclaim any and all liabilities incurred in connection with the use of information contained herein, or otherwise. All risks of such are assumed by the user. Furthermore, nothing contained herein shall be construed as a recommendation to use any process or to manufacture or to use any product in conflict with existing or future patents covering any product or material or its use.